

BAG402

Bayard-Alpert Hot Ion Gauge

The INFICON single Bayard-Alpert Hot Ion Gauge BAG402 covers a wide measurement range from 5×10^{-10} mbar to 2.7×10^{-2} mbar (3.75×10^{-10} Torr to 2×10^{-2} Torr). Choose the INFICON BAG402 for affordable and repeatable process to base pressure measurements in a compact active gauge package. The unique, supported dual filaments offer superior accuracy, longterm stability and longevity. The BAG402 is considered as OEM gauge and direct connection to customers PLC. It is not supported by VGC50x controller series.



ADVANTAGES

- Measurement range from 5×10^{-10} mbar to 2.7×10^{-2} mbar (3.75×10^{-10} Torr to 2×10^{-2} Torr)
- Excellent repeatability in the process pressure range from 10^{-8} ... 10^{-2} mbar of $\pm 5\%$
- Two long-life yttrium oxide coated iridium filaments
- Emission current selection reduces control complexity
- Easy to exchange sensing element with on-board calibration data guarantees high reproducibility
- RoHS compliance

APPLICATIONS

- Pressure measurement in semiconductor process and transfer chambers
- Industrial coating
- General vacuum measurement and control in the low to ultra high vacuum range

BAG402

ORDERING INFORMATION


Sensor Type	BAG402
DN 25 ISO-KF	353-600
DN 40 CF-R	353-601

Replacement Sensor	BAG402
DN 25 ISO-KF	354-484
DN 40 CF-R	354-485

Accessories

Baffle	353-512
Centering ring with baffle DN 25 ISO-KF	211-113

Baffle: Prevents contamination of the sensor, fast and easy installation.



ACCESSORIES

Baffle	353-512
Centering ring with baffle DN 25 ISO-KF	211-113

Baffle:

Prevents contamination of the sensor, fast and easy installation.



BAG402

SPECIFICATIONS

Type	BAG402
Measurement range (air, O ₂ , CO, N ₂)	$5 \times 10^{-10} \dots 2.7 \times 10^{-2}$ mbar ($3.75 \times 10^{-10} \dots 2 \times 10^{-2}$ Torr)
Accuracy 10 ⁻⁸ ... 10 ⁻² mbar	±15% of reading
Repeatability 10 ⁻⁸ ... 10 ⁻² mbar	5% of reading
Degas ¹⁾ p < 7.2 × 10 ⁻⁶ mbar	Electron bombardment, max. 3 min
Pressure, max. bar	2 bar (absolute)
Temperature	
Operation (ambient)	0 ... +50°C
Storage	-20 - +70°C
Bakeout at flange without electronics	80°C
Supply voltage	+20 - +28 / ≤ 0.8 V / A (dc)
Output signal analog	0 - +10.5 V
Measurement range	0.57 ... 8.31 V
Voltage vs. pressure (logarithmic)	1 V / Decade
Error signal	>10 V
Load impedance, min.	10 kΩ
Interface (digital)	Diagnostic port connection, RS232C, Jack connector. 2.5 m, 3-pin
Emission control	Manual via interface
Filament	Two Yt ₂ O ₃ coated Ir
Filament status	LED
Electrical connection	D-Sub, 9-pin, male
Cable length, max.	100 m (330 ft)
Materials exposed to vacuum	Yt ₂ O ₃ , Ir, Pt, Mo, W, NiFe, NiCr, stainless steel, glass
Internal volume KF / CF	24 cm ³ (1.46 in. ³) / 34 cm ³ (2.1 in. ³)
Weight KF / CF	450 g / 710 g
Degree of protection	IP30

¹⁾ Reduced accuracy during degas

BAG402

DIMENSIONS

mm (in.)

BAG402
(D-Sub, 9-pin)

